

## Weight list, Hot-dip galvanised products

In order to simplify the practical work involved in using our EPD, weight information for the constituent products is given below. Weight information for grating is given in a separate weight list that can be found on [weland.se](http://weland.se). By EPD-certifying our products, we create transparency and help our customers actively make climate-smart choices.

### Spiral staircase



#### Standard railing with standard landing

##### Railings

Radius 1000 mm. Grating. Hot-dip galv.  
Radius 1200 mm. Grating. Hot-dip galv.

##### Weight

133 kg/height metre  
158 kg/height metre

##### Example height 3000 mm

16 step heights	incl. landing	399 kg
17 step heights	incl. landing	475 kg



#### Round bar railing with standard landing

##### Railing

Radius 1000 mm. Grating. Hot-dip galv.  
Radius 1200 mm. Grating. Hot-dip galv.

##### Weight

150 kg/height metre  
177 kg/height metre

##### Example height 3000 mm

16 step heights	incl. landing	450 kg
17 step heights	incl. landing	531 kg

### Straight flight staircase



#### Railing, Follower, Width 1000 mm

##### Railing

Railing, one side. Grating. WUC170/3. Hot-dip galv.  
Railing, one side. Grating. WUC170/3. Hot-dip galv.  
Railing, two sides. Grating. WUC170/3. Hot-dip galv.  
Railing, two sides. Grating. WUC170/3. Hot-dip galv.

##### Weight

84 kg/height metre  
104 kg/height metre  
98 kg/height metre  
118 kg/height metre

##### Example height 3000 mm

16 step heights	excl. landing	261 kg
16 step heights	incl. landing	314 kg
16 step heights	excl. landing	294 kg
16 step heights	incl. landing	355 kg

##### Multi-turn staircase

Railing, two sides. Grating. WUC170/3. Hot-dip galvanised Weight: 239 kg/height metre. Example height 6000 mm: 4 staircase loops 28 rises & 4 turning areas. Landing dimensions 2300 x 1000 mm. Railing around landings Incl. support legs, 2 x L6000 mm, 1 x L4500 mm. Weight: 1439 kg



#### Railing, Round bar, Width 1000 mm

##### Railing

Railing, one side. Grating. WUC170/3. Hot-dip galv.  
Railing, one side. Grating. WUC170/3. Hot-dip galv.  
Railing, two sides. Grating. WUC170/3. Hot-dip galv.  
Railing, two sides. Grating. WUC170/3. Hot-dip galv.

##### Weight

95 kg/height metre  
115 kg/height metre  
114 kg/height metre  
140 kg/height metre

##### Example height 3000 mm


16 step heights	excl. landing	284 kg
16 step heights	incl. landing	345 kg
16 step heights	excl. landing	347kg
16 step heights	incl. landing	420 kg

##### Multi-turn staircase

Railing, two sides. Grating. Incl. landings WUC170/3. Hot-dip galvanised Weight: 279 kg/height metre. Example height 6000 mm: 4 staircase loops 28 rises & 4 turning areas. Landing dimensions 2300 x 1000 mm. Railing around landings Incl. support legs, 2 x L6000 mm, 1 x L4500 mm. Weight: 1674 kg.

## Gangway Flex

### Width 1000 mm. Grating H625, hdg



#### Railing

Excl. railing. Incl. support leg 350 mm.  
 Railing, Follower one side. Incl. support leg 350 mm.  
 Railing, Round Bar 1 side Incl. support leg 350 mm.

#### Weight

24 kg/length metre  
 33 kg/length metre  
 41 kg/length metre

#### Example Length 3000 mm

73 kg  
 99 kg  
 123 kg



Railing, Intermediate Rail



Railing, Round Bar

## Wheelchair ramps

### Railing, Standard, Grating N6, Width 1300 mm



#### Railing

Railing on two sides. Incl. support leg.  
 Railing on two sides. Incl. support leg.

#### Weight

62 kg/length metre  
 70 kg/length metre

#### Example Ramp Length 6000 mm

Excl. landing 373 kg  
 Incl. landing 1510x2000 mm 562 kg

## Sectional railing

### Railing height 1100 mm



#### Railing


Follower  
 Round bar (childproof)

#### Weight

8.6 kg/length metre  
 16.6 kg/length metre

#### Example L=4000 + 2000 mm

Incl. a corner 53 kg  
 Incl. a corner 105 kg



Railing, Intermediate Rail



Railing, Round Bar